

Constant Discharge Current	20A	30A	40A	60A
Constant Charge Current	15A	20A	30A	40A
Over Current	2-4 times constant current			
Cell Type			Li-ion	LiFePO4
Charge Voltage			4.2V*Cell Series	3.65V*Cell Series
Over-Charge Protection	Over-charge detection protection voltage	4.25V ± 0.025V	3.65V ± 0.25V	
	Over-charge protection delay time	500~1500ms	500~1500ms	
	Over-charge protection recovery voltage	4.15V ± 0.05V	3.5V ± 0.05V	
Balance	Balance start voltage	4.2V ± 0.025V	3.5V ± 0.05V	
	Balance release voltage	< 4.18V	< 3.5V	
	Balance current	60mA	60mA	
Over-Discharge Protection	Over-discharge detection voltage	3.0 ± 0.1V	2.35 ± 0.1V	
	Over-discharge protection delay time	500~1500ms	500~1500ms	
	Over-discharge protection recovery voltage	3.0 ± 0.1V	2.7 ± 0.1V	
Over-Discharge Current Protection	Over-current protection current	7~13 times	7~13 times	
	Delay time	100~400ms	100~400ms	
	Release conditions	Load off or charge activated		
Short Circuit Protection	Short protection condition	External short with load		
	Short protection delay time	300μs		
	Short protection release condition	Load off > 60s		
Temperature	Working temperature	-20°C ~ 75°C		
	Max discharge working temperature	75°C ± 5°C		
Self-Current Consumption	Working current consumption	Less than 40mA		
	Sleep current consumption	Less than 30μA		
Dimensions		108mm*65mm*10mm 108mm*65mm*15mm (40A,60A)		